QUICKFIX MRT® POST 48 mm - WITH MESH





듣

CHARACTERSITICS



	Quickfix MRT® 48 Post		
Diameter	48 mm		
Arm post	Folded arm post Length: 400 mm Option to install with barbed wire Angle: 135° to the post		

FINISHING FEATURES

POWDER COATING

• 10 standard RAL colours. (More than 200 RAL colours available).







- Steel galvanized sheet according to EN 10346 standard.
- Polyester powder coating by electrostatic application with microcrystalline phosphatation. Thickness: 80 microns minimum.

T STANDARD DIMENSIONS

Quickfix MRT® 48 System			
Post Ø48 mm		End-turner Ø38 mm	
700 900 1,100 1,300 1,500	1,750 2,000 2,150 2,350 2,500	1,200 1,450 1,800 2,400	







ACCESSORIES

fyación

QUICKFIX MRT® POLYAMIDE BRACKET

- Material: Polyamide
- · Included screws
- · Colours: White or Green.

QUICKFIX MRT® METALLIC BRACKET

- Material: Galvanized steel or galvanized and coated steel
- Included screws
- RAL colours: Green 6005, Grey 7016 or Galvanized



QUICKFIX MRT® MESH FIXING ACCESSORY

- Material: Galvanized steel or galvanized and coated steel
- Included screws
- RAL colours: Green 6005 or Galvanized



bases

QUICKFIX MRT® POLYAMIDE BASE

- Material: Polyamide
- Measures: Ø120 mm
- Included screws
- Colours: Green, White or Grey



fyación

QUICKFIX MRT® STAPLES AND STAPLES TOOL

• Staples material: Galvanized steel or stainless steel.





METALLIC TENSIONER

- Material: Galvanized steel or galvanized and coated steel
- RAL colours: Green 6005 or Galvanized

QUICKFIX MRT® 38mm END-TURNER

- Material: Galvanized steel or galvanized and coated steel
- RAL colours: The same as post

bases

QUICKFIX MRT® POLYAMIDE END-TURNER BASE

- Material: Polyamide
- Included screws
- Colour: Green





%

INSTALLATION



How to calculate the number of posts I need for an installation?

EndReinforcementAngleIntermediate1 al the beginning + 1 at the end1 every 30 m1 each corner1 every 3 m



