

QUICKFIX MRT® POST

48 mm - WITH PANELS




CHARACTERISTICS



To dig in



With welded base
125x125 mm

Quickfix MRT® 48 Post	
Diameter	48 mm
Arm post	Folded arm post Length: 400 mm Option to install with barbed wire Angle: 135° to the post
	



FINISHING FEATURES

POWDER COATING

- 10 standard RAL colours. (More than 200 RAL colours available).



- Steel galvanized sheet according to EN 10346 standard.
- Polyester powder coating by electrostatic application with microcrystalline phosphatation.
Thickness: 80 microns minimum.

STANDARD DIMENSIONS

Panel height	Quickfix MRT® 48 post height			
	To dig in		With base	
	Short	Long	Embedded	Welded
625	900	1,100	700	-
800	1,100	1,300	900	-
825	1,100	1,300	900	-
925	1,300	-	-	1,050
1,000	1,300	1,500	1,100	1,050
1,025	1,300	1,500	1,100	1,050
1,225	1,500	1,700	1,300	1,250
1,400	1,850	1,850	-	-
1,525	1,850	2,000	-	1,550
1,600	2,000	2,150	-	-
1,725	2,000	2,150	-	1,850
1,800	2,350	2,350	-	-
2,000	2,500	2,500	-	2,050
2,025	2,500	-	-	2,050



resources
Installation
tips



ACCESSORIES

fixing

QUICKFIX MRT® POLYAMIDE BRACKET

- Material: Polyamide
- Included screws
- Colours: White or Green



QUICKFIX MRT® METALLIC BRACKET

- Material: Galvanized steel or Galvanized and coated steel
- Included screws
- Standard RAL colours: Green 6005, Grey 7016 or Galvanized



QUICKFIX MRT® PANEL FIXING ACCESSORY

- Material: Galvanized steel or Galvanized and coated steel
- Included screws
- RAL colours



base

QUICKFIX MRT® POLYAMIDE BASE

- Material: Polyamide
- Measures: Ø125 mm
- Included screws
- Only for enclosures lower than 1525 mm



INSTALLATION

HÉRCULES® AND BRICO-HÉRCULES® PANELS

Distance between post axis for 2.500 mm panels

- Quickfix MRT® Bracket: 2.520 mm
- Quickfix MRT® Fixing Accessory: 2.550 mm (+/-10)

ECO AND EXOTIC® PANELS

Distance between post axis for 2.000 mm panels

- Quickfix MRT® Bracket: 2.020 mm
- Quickfix MRT® Fixing Accessory: 2.050 mm (+10/-20)

TWIN WIRE 6/5/6 PANELS

Distance between post axis for 2.490 mm panels

- Quickfix MRT® Bracket: 2.510 mm
- Quickfix MRT® Fixing Accessory: 2.540 mm (+/-10)

TWIN WIRE 8/6/8 PANELS

Distance between post axis for 2.490 mm panels

- Quickfix MRT® Fixing Accessory: 2.540 mm (+/-10)