

EASYCLIP® POST



WARRANTY
10 YEARS



CHARACTERISTICS



To dig in



With welded base
125x125 mm

Section	66 x 50 mm	
Arm post	Embedded arm post Kit with aluminium insert Length: 650 mm Possible installation of panels or barbed wire Angle: 135° to the post	Double welded arm post Length: 650 mm. Possible installation of panels or barbed wire Angle: 135° to the post 90° between arms
		

Arms come ready to install barbed wire with the help of the Quickfix MRT® staple.



¿How to use the hooked cap?

The posts has a hooked cap, to hang the top of the panel while it is installed.



FINISHING FEATURES

POWDER COATING

- 10 standard RAL colours. (More than 200 RAL colours available).
- Steel galvanized sheet according to EN 10346 standard.
- Polyester powder coating by electrostatic application with microcrystalline phosphatation. Thickness: 80 microns minimum.



STANDARD DIMENSIONS

Panel height (mm)	Post length (mm)				No. of brackets per post	
	To dig in		With base		End	Intermediate
	Short	Long	Embedded	Welded		
625	900	1,100	700	650	2	4
800	1,100	1,300	900	850		
825	1,100	1,300	900	850		
925	1,300	1,600	-	-		
1,000	1,300	1,600	1,100	1,050		
1,025	1,300	1,600	1,100	1,050		
1,225	1,600	-	1,300	1,250	3	6
1,400	-	2,000	-	-		
1,525	-	2,200	1,600	1,550		
1,600	2,000	-	-	-		
1,725	2,200	2,400	-	1,750		
1,800	2,200	2,400	-	-		
1,925	2,400	2,500	-	-	4	8
2,000	2,400	2,500	-	2,050		
2,425	-	3,200	-	-		

ACCESSORIES

fixing

EASYCLIP® ALUMINIUM BRACKET

- Included screws
- Angles up to 66°
- RAL standard colours



EASYCLIP® POLYAMIDE BRACKET

- Included screws
- Angles up to 66°
- RAL colours: Green 6005, Black 9005 or White 9010



EASYCLIP® STAINLESS BRACKET

- Angles up to 66°
- RAL standard colours



bases

EASYCLIP® ALUMINIUM BASE

- Measures: 148x125 mm
- Distance between screws: 90 mm
- Included screws
- RAL standard colours



EASYCLIP® STEEL BASE

- Measures: 148x125 mm
- Distance between screws: 90 mm
- Not included screws
- RAL standard colours



EASYCLIP® STEEL FRONTAL BASE

- Material: Galvanized steel
- Distance between screws: 90 mm
- Not included screws
- Not included screws



INSTALLATION

HÉRCULES® AND BRICO-HÉRCULES® PANEL

Distance between post axis for 2.500 mm panels

- Brackets Easyclip®: 2.520 mm

ECO AND EXOTIC® PANEL

Distance between post axis for 2.000 mm panels

- Brackets Easyclip®: 2.020 mm

TWIN WIRE 6/5/6 AND 8/6/8 PANELS

Distance between post axis for 2.490 mm panels

- Brackets Easyclip®: 2.510 mm

resources

Easyclip® installation video

