



# HÉRCULES® POST



## CHARACTERISTICS



Section	60 x 40 mm	
Arm post	<b>Embedded arm post</b> Kit with aluminium insert Length: 650 mm Option to install with panels or barbed wire Angle: 135° to the post	<b>Double welded arm post</b> Length: 650 mm Option to install with panels or barbed wire. Angle: 135° to the post, 90° between arms
		

The arms come ready to install barbed wire with the help of the Quickfix® staple

## FINISHING FEATURES

### POWDER COATING

- 10 standard RAL colours. (More than 200 RAL colours available).

- Steel galvanized sheet according to EN 10346 standard.
- Polyester powder coating by electrostatic application with microcrystalline phosphatation. Thickness: 80 microns minimum.



## STANDARD DIMENSIONS

Panel height	Post length				No. of fixing accessories per post
	To dig in		With base		
	Short	Long	Embedded	Welded	
625	850	1,050	650	650	2
825	1,050	1,250	850	850	
925	1,250	1,550	-	-	
1,000	1,250	1,550	1,050	1,050	
1,025	1,250	1,550	1,050	1,050	
1,225	1,550	1,750	1,250	1,250	3
1,400	1,750	2,050	-	-	
1,525	1,850	2,050	1,550	1,550	
1,600	-	2,050	-	-	
1,725	2,050	2,350	-	1,750	
1,800	-	2,350	-	-	
1,925	2,350	2,550	-	-	
2,000	2,350	2,550	-	-	4
2,025	2,350	2,550	-	2,050	
2,425	3,000	3,200	-	-	

### resources

Installation tips



## ACCESSORIES

### HÉRCULES® BRACKET

- Material: Polyamide
- Included screws
- 90° angles
- RAL colours: Green 6005, Grey 7016, Grey 7045, White 9003 and Black 9005



### ULTRAFIX® BRACKET

- Material: Galvanized steel
- Included screws
- 90° angles
- RAL standard colours



### HÉRCULES® STAPLE

- Material: Galvanized steel
- Not included screws
- 90° angles
- RAL standard colours



### HÉRCULES® ALUMINIUM BASE

- Material: Aluminium
- Measures: 125x125 mm
- Included screws



### HÉRCULES® STEEL BASE

- Material: Galvanized steel
- Measures: 125x125 mm
- Not included screws



### HÉRCULES® POST UNION

- Material: Zinc plated steel 10 micron (1.50 mm thickness)
- To lift fences made with Hercules posts (1,50 mm thickness)



## INSTALLATION

### HÉRCULES® AND BRICO-HÉRCULES® PANEL

#### Distance between post axis for 2.500 mm panels

- Hercules® and Ultrafix® Bracket: 2,525 mm (+10/-20)
- Hercules® Staple: 2,525 mm (+/-10)

### TWIN WIRE 6/5/6 PANEL

#### Distance between post axis for 2.490 mm panels

- Hercules® and Ultrafix® Bracket: 2,515 mm (+10/-20)
- Hercules® Staple: 2,515 mm (+/-10)

! The fastening slots are used only when the panels form 90° corners.

