

PROFIX® POST



CHARACTERISTICS

The Profix® Post requires no fastening accessories and it is an inviolable system.

Section	66 x 50 mm
---------	------------



Once the cement has dried, the Profix® blockers can be removed and reused in the next installation.



resources

Profix® Installation video



FINISHING FEATURES

POWDER COATING

- 10 standard RAL colours. (More than 200 RAL colours available).
- Steel galvanized sheet according to EN 10346 standard.
- Polyester powder coating by electrostatic application with microcrystalline phosphatation. Thickness: 80 microns minimum.



STANDARD DIMENSIONS

Panel height (mm)	Post length (mm)			
	To dig in		With base	
	Short	Long	Embedded	Welded
625	900	1,100	700	700
800	1,100	1,300	900	900
825	1,100	1,300	900	900
925	1,300	-	-	-
1,000	1,300	-	1,100	1,100
1,025	1,300	1,700	1,100	1,100
1,225	1,700	-	1,300	1,300
1,400	-	2,000	-	-
1,525	-	2,000	1,700	1,600
1,600	2,000	-	-	-
1,725	2,000	2,200	-	1,800
1,800	2,200	2,400	-	-
1,925	2,400	2,500	-	-
2,000	2,400	2,500 - 2,700	-	2,100
2,025	2,400	2,500 - 2,700	-	2,100

ACCESSORIES

installation

PROFIX® BLOCKER

- Material: Polyamide



bases

PROFIX® ALUMINIUM BASE

- Measures: 148x125 mm
- Distance between screws: 90 mm
- Included screws
- RAL standard colours



PROFIX® ECO BASE

- Material: Aluminium
- Measure: 110x107,5 mm
- Included screws
- RAL standard colours



bases

PROFIX® STEEL BASE

- Measures: 148x125 mm
- Distance between screws: 90 mm
- Not included screws
- RAL standard colours



PROFIX® STEEL FRONTAL BASE

- Measures: 148x125 mm
- Distance between screws: 90 mm
- Not included screws
- RAL standard colours



spare parts

PROFIX® REPAIR POST

- Length: 3.200 mm
- RAL standard colours



INSTALLATION

HÉRCULES® AND BRICO-HÉRCULES® PANELS

Distance between post axis for 2.500 mm panels

- 2.540 mm

ECO AND EXOTIC® PANELS

Distance between post axis for 2.000 mm panels

- 2.040 mm

TWIN WIRE 6/5/6 PANEL

Distance between post axis for 2.490 mm panels

- 2.530 mm



If the panel has bends, they should be placed facing outwards.