SWING GATE CLASSIC PRO





CHARACTERISTICS

- · Manual access.
- Variable post section according to the gate size.
- Gate supplied preassembled and easy access to its Declaration of Performance.
- Posts to dig in, welded base plated option.
- According to many national accessibility regulations for People with Reduced Mobility, request us for more information.



Vertical bars: 25 x 25 x 1.0 mm.

Distance between bars: maximum 100 mm.



+ COMPONENTS

LOCINOX® LOCK

- European cylinder: 54 mm (symmetric 27-27) keyed to differ.
- Stainless mechanism.
- Adjustable from 40 to 60 mm.
- Easily reversible latch without disassembly.

LOCINOX® HINGE

Our fall-proof system for long leaves: with an additional third hinge.

- · Hot dip galvanized.
- 180° opening.
- Fully reversible.
- The eye-bolt also changes to adapt to the posts size.



GROUND STOP AND DROP BOLT:

(double leaf gates only).



| SINGLE LEAF GATE

POST SIZE / HEIGHT (mm)		Nominal gate width (m)								
		1.0	1.2	1.5	2.0	3.0	4.0	5.0		
Gate height (m)	1.0		60x60	/ 1,430		80x80 / 1,480*	-	-		
	1.2		60x60	/ 1,630		80x80 / 1,680	100x100 / 1,730*	-		
	1.5		60x60 / 1,930		80x80 / 1,980	100x100 / 2,030	120x120 / 2,080*	-		
	1.7	60x60 / 2,130		80x80 / 2,180		120x120 / 2,280	120x120 / 2,330	140x140 / 2,380*		
	2.0		80x80 / 2,480		100x100 / 2,530	120x120 / 2,580	140x140 / 2,680	140x140 / 2,680*		
	2.5	80x80 / 2,980	100x100	0 / 3,030	120x120 / 3,080	140x140/3,180	150x150 / 3,230	160x160/3,280*		
	3.0	100x100	0/3,530	120x120 / 3,580	120x120 / 3,630	140x140/3,680	160x160/3,780	180x180 / 3,830		
FRAME SIZE (mm)		50x50			60x60		60x60 vertical - 60x80 horizontal			

^{*} Gates with posts of this dimension have 3 hinges to provide more security.

|| DOUBLE LEAF GATE

POST SIZE / HEIGHT (mm)		Nominal gate width (m)								
		2.0	3.0	4.0	5.0	6.0	8.0	10,0		
Gate height (m)	1.0	60x60 / 1,430	80x80 / 1,480	60x60	/ 1,430	80x80 / 1,480*	-	-		
	1.2	60x60 / 1,630	80x80 / 1,680	100x100 / 1,730	80x80 / 1,680		100x100 / 1,730*	-		
	1.5	60x60 / 1,930	80x80 / 1,980	100x100 / 2,030			120x120 / 2,080*	-		
	1.7	60x60 / 2,130	80x80 / 2,180	100x100 / 2,230		120x120 / 2,280	120x120 / 2,330	140x140 / 2,380*		
	2.0	80x80 / 2,480		100x100 / 2,530	120x120 / 2,580		140x140 / 2,680	140x140 / 2,680*		
	2.5	80x80 / 2,980	100x100 / 3,030	120x120 / 3,080	120x120 / 3,130	140x140/3,180	150x150 / 3,230	160x160 / 3,280*		
	3.0	100x100/3,530	120x120 / 3,580	120x120 / 3,630	140x140	0/3,680	160x160 / 3,780	180x180 / 3,830		

FRAME SIZE (mm) 50x50 60x60 vertical - 60x80 horization



How to calculate the TOTAL GATE WIDTH?

Single leaf nominal gate width $(mm) + (2 \times post size (mm)) + 100 mm$ Double leaf nominal gate width $(mm) + (2 \times post size (mm)) + 160 mm$



How to calculate the PASSAGE?

* Gates with posts of this dimension have 3 hinges to provide more security.

Single leaf nominal gate width (mm) + 46,7 mm

Double leaf nominal gate width (mm) + 160 mm



ASSOCIATED PRODUCTS

DEFENSIVE CREST:Bolted to the top frame, reinforces the security.

HYDRAULIC GATE CLOSER



GATE HOLD-BACK

TRIANGULAR CYLINDER SET



BASE PLATE: Suitable for single leaf gates with a 1.2 m maximum width.



FINISHING FEATURES

- Steel galvanized sheet according to EN 10346 standards.
- Polyester powder coating, microcrystalline phosphating by a process of electrostatic application. Polyester thickness: 80 microns minimum.









