SWING GATE RONDO PLUS





CHARACTERISTICS

- Manual access.
- Variable post section according to the gate size.
- Gate supplied preassembled and easy access to its Declaration of Performance.
- Posts to dig in, welded base plated option.
- According to many national accessibility regulations for People with Reduced Mobility, request us for more information.

filling

Not crossing round bars: Ø 25 x 1.5 mm.

Distance between extreme vertical bars and frame: 95 mm.

Rest of free distance between bars: maximum 75 mm.



+ COMPONENTS

LOCINOX® LOCK

- European cylinder: 54 mm (symmetric 27-27) keyed to differ.
- Stainless mechanism.
- Adjustable from 40 to 60 mm.
- Easily reversible latch without disassembly.

LOCINOX® HINGE

Our fall-proof system for long leaves: with an additional third hinge.

- · Hot dip galvanized.
- 180° opening.
- Fully reversible.
- The eye-bolt also changes to adapt to the posts size.



GROUND STOP AND DROP BOLT: (double leaf gates only).



| SINGLE LEAF GATE

POST SIZE / HEIGHT (mm)		Nominal gate width (m)							
		1.0	1.2	1.5	2.0	3.0	4.0	5.0	
Gate height (m)	1.0	60x60 / 1,430				80x80 / 1,480*	-	-	
	1.2	60x60 / 1,630			80x80 / 1,680	100x100 / 1,730	100x100 / 1,730*	-	
	1.5	60x60	/ 1,930 80x80		/ 1,980	100x100 / 2,030	120x120 / 2,080*	-	
	1.7	60x60 / 2,130	80x80 / 2,180		100x100 / 2,230	120x120 / 2,280	120x120 / 2,330*	140x140 / 2,380*	
	2.0	80x80 / 2,480	80x80 / 2,480		100x100 / 2,530	120x120 / 2,630	140x140 / 2,680	150x150 / 2,730*	
	2.5	80x80 / 2,980	100x100 / 3,030		120x120 / 3,130	140x140 / 3,180	150x150 / 3,230	180x180 / 3,330*	
	3.0	100x100 / 3,530	120x120 / 3,580		140x140 / 3,680	150x150 / 3,730	180x180 / 3,830	200x200 / 3,880*	
EDAME CIZE ()		E0E0			/ 0	./0	/0 /0 : 1	/000	

FRAME SIZE (mm) 50x50 60x60 vertical - 60x80 horizontal

|| DOUBLE LEAF GATE

POST SIZE / HEIGHT (mm)		Nominal gate width (m)							
		2.0	3.0	4.0	5.0	6.0	8.0	10,0	
Gate height (m)	1.0	60x60 / 1,430	80x80 / 1,480	60x60 / 1,430	80x80 / 1,480	80x80 / 1,480*	=	-	
	1.2	60x60 / 1,630	80x80 / 1,680	100x100 / 1,730	80x80 / 1,680	100x100 / 1,730	100x100 / 1,730*	-	
	1.5	60x60 / 1,930	80x80 / 1,980	100x100 / 2,030			120x120 / 2,080*	-	
	1.7	60x60 / 2,130	80x80 / 2,180	100x100 / 2,230		120x120 / 2,280	120x120 / 2,330*	140x140 / 2,380*	
	2.0	80x80 / 2,480		100x100 / 2,530	120x120 / 2,580	120x120 / 2,630	140x140 / 2,680	150x150 / 2,730*	
	2.5	80x80 / 2,980	100x100 / 3,030	120x120 / 3,130		150x150 / 3,230	180x180 / 3,330*		
	3.0	100x100 / 3,530	120x120 / 3,580	140x140 / 3,680		150x150 / 3,730	180x180 / 3,830	200x200 / 3,880*	

FRAME SIZE (mm)	50x50	60x60	60x60 vertical - 60x80 horizontal
-----------------	-------	-------	-----------------------------------



How to calculate the TOTAL GATE WIDTH? *

Single leaf nominal gate width (mm) + (2 x post size (mm)) + 100 mm

Double leaf nominal gate width (mm) + (2 x post size (mm)) + 160 mm



How to calculate the PASSAGE? *

Single leaf nominal gate width (mm) + 46,7 mm

Double leaf nominal gate width (mm) + 160 mm

* For 5.0 m single leaf gate width and 3.0 m height, subtract 15 mm from the total. For 10.0 m double leaf gate width and 3.0 m height, subtract 25 mm from the total.

* Gates with posts of this dimension have 3 hinges to provide more security.

st Gates with posts of this dimension have 3 hinges to provide more security.



ASSOCIATED PRODUCTS

DEFENSIVE CREST:Bolted to the top frame, reinforces the security.

HYDRAULIC GATE CLOSER



GATE HOLD-BACK CATCH



TRIANGULAR CYLINDER SET



BASE PLATE:

Suitable for single leaf gates with a 1.2 m maximum width.



FINISHING FEATURES

- Steel galvanized sheet according to EN 10346 standards.
- Polyester powder coating, microcrystalline phosphating by a process of electrostatic application. Polyester thickness: 80 microns minimum.









