SWING GATE DOMINO 1|5



CHARACTERISTICS

- Manual access.
- Variable post section according to the gate size.
- Gate supplied preassembled and easy access to its Declaration of Performance.
- Posts to dig in, welded base plated option.
- According to many national accessibility regulations for People with Reduced Mobility, request us for more information.



Crossing round bars: 50 x 10 mm Distance between bars: maximum 110 mm.



+ COMPONENTS

LOCINOX® LOCK

- European cylinder: 54 mm (symmetric 27-27) keyed to differ.
- Stainless mechanism.
- Adjustable from 40 to 60 mm.
- Easily reversible latch without disassembly.



LOCINOX® HINGE

Our fall-proof system for long leaves: with an additional third hinge.

- Hot dip galvanized.
- 180° opening.
- Fully reversible.
- The eye-bolt also changes to adapt to the posts size.

GROUND STOP AND DROP BOLT:

(double leaf gates only).





SINGLE LEAF GATE


| POST SIZE / HEIGHT (mm) | | Nominal gate width (m) | | | | | | | | |
|----------------------------|-----|------------------------|---------------|-----------------|-----------------|------------------|-----------------------------------|------------------|--|--|
| | | 1,0 | 1,2 | 1,5 | 2,0 | 3,0 | 4,0 | 5,0 | | |
| Gate height (m) | 1,0 | | 60x60 | / 1.430 | | 80x80 / 1.480* | = | - | | |
| | 1,2 | | 60x60 / 1.630 | | 80x80 / 1.680 | 100x100 / 1.730* | - | - | | |
| | 1,5 | 60x60 / 1.930 | | 80x80 / 1.980 | 100x100 / 2.030 | 120x120 / 2.080 | 120x120/2.130* | = | | |
| | 1,7 | 60x60 / 2.130 80x80 / | | / 2.180 | 100x100 / 2.230 | 120x120 / 2.280 | 140x140/2.380* | - | | |
| | 2,0 | 80x80 / 2.480 | | 100x100 / 2.530 | 120x120 / 2.580 | 120x120 / 2.630 | 140x140/2.680* | - | | |
| | 2,5 | 100x100 / 3.030 | | 120x120/3.080 | 120x120/3.130 | 140x140 / 3.180 | 160x160/3.280 | 180x180 / 3.330* | | |
| | 3,0 | 100x100/3.530 | 120x120/3.580 | 120x120/3.630 | 140x140 / 3.680 | 150x150 / 3.730 | 180x180 / 3.830 | - | | |
| | | | | | | | | | | |
| FRAME SIZE (mm) | | 50x50 | | | 60x60 | | 60x60 vertical - 60x80 horizontal | | | |

 $\ensuremath{^*}\xspace$ Gates with posts of this dimension have 3 hinges to provide more security.

|| DOUBLE LEAF GATE

| POST SIZE / HEIGHT (mm) | | Nominal gate width (m) | | | | | | | | |
|----------------------------|-----|------------------------|-----------------|-----------------|---------------------------|------------------|-----------------------------------|----------------|--|--|
| | | 2.0 | 3.0 | 4.0 | 5.0 | 6.0 | 8.0 | 10,0 | | |
| Gate height (m) | 1.0 | 60x60 / 1.430 | 80x80 / 1.480 | 60x60 / 1.430 | 80x80 / 1.480* | | - | - | | |
| | 1.2 | 60x60 / 1.630 | 80x80 / 1.680 | 100x100/1.730 | 80x80 / 1.680 | 100x100 / 1.730* | - | - | | |
| | 1.5 | 60x60 / 1.930 | 80x80 / 1.980 | 100x100 | 0 / 2.030 120x120 / 2.080 | | 120x120 / 2.130* | - | | |
| | 1.7 | 60x60/2.130 | 80x80 / 2.180 | 100x100 / 2.230 | 120x120 |) / 2.280 | 140x140 / 2.380* | - | | |
| | 2.0 | 80x80 / 2.480 | 100x100 / 2.530 | 120x120 | / 2.580 | 120x120/2.630 | 140x140/2.680* | - | | |
| | 2.5 | 100x100 / 3.030 | 120x120/3.080 | 120x120/3.130 | 140x140 / 3.180 | | 160x160/3.280 | 180x180/3.330* | | |
| | 3.0 | 100x100/3.530 | 120x120/3.630 | 140x140 | / 3.680 | 150x150 / 3.730 | 180x180 / 3.830 | - | | |
| | | | | | | | | | | |
| FRAME SIZE (mm) | | 50x50 | | 60x60 | | | 60x60 vertical - 60x80 horizontal | | | |

st Gates with posts of this dimension have 3 hinges to provide more security.



- Steel galvanized sheet according to EN 10346 standards.
- Polyester powder coating, microcrystalline phosphating by a process of electrostatic application. Polyester thickness: 80 microns minimum.

